




LTE Cat.1 Vehicle Tracker

LTE Cat.1 (fall back to 3G/2G) GPS tracker with BLE for comprehensive vehicle tracking applications.

HYN001 Series

- Dimensions: 106*43.2*13.5mm
- Weight: 66±2g
- Operating Voltage: 8V to 32V DC
- Operating Temperature: -30°C ~ +80°C



HYN001 is a well designed LTE Cat.1 GPS tracker used for all kinds of vehicle tracking applications. It has built in BLE and backup battery. The multiple I/O interface support various external sensors. Also the compact size ensures conceal and easy installation. The HYN001 has good quality and excellent GPS performance, it has passed major operators certifications in the world.

Application



Vehicle Tracking



Ship Tracking



Fleet Management



Cold Chain



Logistics Monitoring

Product Information

Model Name	HYN001 Series
Dimension	106*43.2*13.5mm
Weight	66±2g

General Specification

Waterproof	IP65
Backup Battery	200mAh
Operating Voltage	8V to 32V DC
Operating Temperature(With external DC power)	-30°C~ +80°C

Cellular Specification

Frequency Bands	HYN001	LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE-TDD: B40 WCDMA: B1/B2/B5/B8 EGPRS: 850/900/1800/1900 MHz
	HYN001-E	LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8 EGPRS: 900/1800MHz

Data Transfer (Max)	LTE(Mbps):10(DL)/5(UL) HSPA+(Mbps):42(DL)/5.76(UL) WCDMA(Kbps):384(DL)/384(UL) GPRS/EDGE(Kbps):236.8(DL)/236.8(UL)
---------------------	---

GNSS Specification

GNSS	Qualcomm MDM9207
Sensitivity	Tracking: -158 dBm Cold start: -148 dBm
Position Accuracy(CEP)	Autonomous: < 2.5m (CEP50)
TTFF(Open Sky) (Average)	Cold start: <35s Hot start: <1s

Hardware Specification

Digital Input	1 positive trigger for ignition input
Digital Output	1 digital output, open drain 1A MAX
Configurable Input/ Output	1 configurable input/ output (open drain 1A MAX)
Analog Input	1 Analog input
Cellular Antenna	Internal
GNSS Antenna	Internal
BLE	5.0
LED	*2 (CEL and GPS)

Air Interface Protocol

Transmit Protocol	TCP, UDP, SMS
Scheduled Report	Report position and status according to preset intervals
Geo-fences	Geo-fence alarm, support circular and polygon regions
Power On Report	Report when device is powered on
Tow Alarm	Support
Driving Behavior Monitoring	Support
Crash Detection	Support
Other Alarm	Special Alarm based on digital input connection